



SPECIFICATIONS

Capacity:	130,000 lbs.	Trailer Weight:	26,500 lbs.
Deck Width	8 ft. 6 in. Length: 25 ft. Height: 24 in. (Loaded)		
Frame	Mainrails: Four fabricated 16" Deep cambered I-Beam, 100,000 P.S.I. T-1 steel, Boom Well,		
Crossmembers	10" x 12 lbs. per ft. I-Beam, pierced through mainbeam (24" spacing Std.)		
Gooseneck Length	110" & 90" Swing Clearance With Connections For Future 60" Flip Gooseneck Extension		
Decking	Full 2" Apitong Decking with Expanded Metal Center		
Wiring Harness	Sealed L.E.D. Lights & USA Star PLUS Sealed Modular Wiring Harness w/ 7-Way ATA Plug		
Front Ramps	Front Flip w/ Grousers (Wood filled is available)		
Hydraulics	Wetline hook-up for tractor PTO operation • REQUIREMENT: Low Flow/High Pressure System		
Hydraulic Cylinders	Two Main 9", One 3" Locking, One 4" Gooseneck Support		
Controls	Control Valve eye level		
Lift Axle	Air Lift 3rd Axle		
Tie Down	7 per side - Patented "ROTO RINGS"® Swivel 360°		
Outriggers	Cast Steel (Locks both in and out position) -- HD Pullout 1st Outrigger		
Tailboard	Complete Setup For Future Flip / Tandem Spread Axle		
Colors	Black, Yellow, Blue (standard) Imron Paint		

RUNNING GEAR

Tires	Twelve Yokohama Super Steel 275/70R22.5 (H) Steel Belted Radial
Hubs/Wheels	Six Disc Type Hubs, Twelve 8.25 x 22.5 Disc Type Wheels, Stemco Oil Seals, Hub Piloted
Suspension	Air Ride (Combined Capacity 75,000 lbs.) Dump Valve, Air Lift 3rd Axle
Axles	Three 5" diameter 25,000 lbs. each, H.M. series bearings
Brakes	16 1/2" x 7" Air, "S" Cam., Auto Slack Adjusters
ALL WHEEL ABS	Anti-lock brake system 4S3M, Sensors on (2) Axles, 3 modulator valves
Parking Brake	Spring Brakes on All Wheels

OPTIONS

- Additional Deck Length: (26'-27'-28' Optional Lengths)
- Additional Deck Width: (108" w/ 102" axles or 108" axles) - (120" w/ 120" axles)
- Gooseneck Fenders
- Power Pack: 11hp, 12hp Kohler, 13hp Honda, or 16hp Kohler (Combination Power Pack/Wet Kit Available)
- Lockable Tool & Chain Storage: Forward center deck area (1 or 2 compartments)
- Additional "ROTO-RINGS"®
- Spare Tire & Disc Wheel 275/70R22.5 (H) Optional: Spare Tire Carrier
- Wheel Covers (Raised)
- Oak Decking in lieu of Apitong
- Paint (other than standard Black, Yellow, Blue) Price on Request

